

# SV60-V2 Next Generation Portable Solids Pump



## Features

- ATEX Zone 2/CE conformity
- Next Generation Pneumatics
- 100% compressed air operation
- Multipurpose vacuum pump
- Intrinsically safe
- Fully automatic
- Versatile
- No internal moving components
- Minimal maintenance
- High vacuum and high airflow
- Recovers material from up to 50 metres (164ft)
- Delivers up to 500 metres (1640ft)

## About

The SV60V Portable Solids Pump is a one man vacuum loading, pressure discharge pump capable of recovering and transferring up to 27 m<sup>3</sup>/hr (119USGPM) @ SG1.0.

The SV60V Portable Solids Pump is 100% air powered and operated, generates up to 25" Hg+ of vacuum combined with high airflow which allows the unit to transfer materials ranging from mining slurries and oil sludge through to cementitious powders and grains.

The SV60V Portable Solids Pump is employed worldwide servicing farms, mines, drill rigs, municipal, industrial and construction sites.

Next Generation Pneumatic control box provides a more user friendly system with new countdown timers, indicators showing pump cycle, increased safety, usability & serviceability. Standardized across our SV30, SV60, SV60-V & SV110-V ranges, completely interchangeable & quick connectivity minimizing down time.

## Applications

- Spillage recovery and transfer
- Sump cleaning and desilting
- Tank cleaning and sludge extraction
- Pneumatic excavation and dewatering
- WBM / OBM / Drill Cuttings transfer

## New Options

- Next Generation Pneumatics Control box retro fit kits to upgrade existing pumps
- Low (adjustable) discharge pressure
- Reduced air consumption
- Spare parts kit includes quick change control box, reducing down time.

## Technical Data

- Height 110 cm (44")
- Width 73 cm (29")
- Length 93 cm (37")
- Weight 190 kg (418 lb)
- Throughput capacity up to 27m<sup>3</sup>/hr (119USGM) @ SG1.0
- Air consumption 150cfm (71L/sec) at minimum 85psi (6bar) to 100psi (7bar) at the pump
- Air supply connection 25mm (1")
- Up to 25" Hg+ (85kPa) vacuum
- Suction 75 mm (3") BSP/Type B camlock
- Discharge 75 mm (3") BSP/Type A camlock
- Handles solids to 50 mm (2")
- Carbon steel vessel
- Also available in 316 stainless materials of construction
- Skid mounted/roll frame weights/ dimensions on request